



# Additel 760

## Automatic Handheld Pressure Calibrator

### Selection Guide

Model	760-LLP	760-LLP-DL	760-D	760-D-DL	760-MA	760-MA-DL
<b>Features</b>						
<b>Pressure Range<sup>[1]</sup></b>	±30 in H <sub>2</sub> O (±75 mbar)	±30 in H <sub>2</sub> O (±75 mbar)	-12.5 to 35 psi (-0.86 to 2.5 bar)	-12.5 to 35 psi (-0.86 to 2.5 bar)	-12.5 to 300 psig (-0.86 to 20 bar)	-12.5 to 300 psig (-0.86 to 20 bar)
<b>Accuracy (%FS)</b>	0.05 <sup>[1]</sup>	0.05 <sup>[1]</sup>	0.02 <sup>[1]</sup>	0.02 <sup>[1]</sup>	0.02 <sup>[1][3]</sup>	0.02 <sup>[1][3]</sup>
<b>Stability (%FS)</b>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>	<0.005 <sup>[2]</sup>
<b>Gauge Pressure</b>	●	●	●	●	●	●
<b>Differential Pressure</b>	●	●	●	●		
<b>Absolute Pressure</b>					●	●
<b>Barometric Pressure</b>					●	●
<b>Removable Internal Module</b>	●	●	●	●	●	●
<b>External Pressure Module</b>	●	●	●	●	●	●
<b>Temperature Compensated</b>	●	●	●	●	●	●
<b>Built-in Electrical Pump</b>	●	●	●	●	●	●
<b>Built-in Filter</b>	●	●	●	●	●	●
<b>Built-in Liquid Trap</b>	●	●	●	●	●	●
<b>Source/Simulate 24 mA</b>	●	●	●	●	●	●
<b>Measure mA or V</b>	●	●	●	●	●	●
<b>24V Loop power</b>	●	●	●	●	●	●
<b>Pressure switch test</b>	●	●	●	●	●	●
<b>HART Communication</b>		●		●		●
<b>Task Documentation</b>		●		●		●
<b>Data Logging</b>		●		●		●
<b>Channels</b>	4	4	4	4	4	4
<b>USB, Wi-Fi, and Bluetooth</b>	●	●	●	●	●	●

[1] FS specification applies to the span of the module range.

[2] Stability based on FS of the internal pressure module. Internal module is switchable.

[3] Specification based on gauge measurement. An additional 60 pa uncertainty will need to be included when measuring in absolute mode.